

Appl. No. 10/772965
Reply to Action dated 9/14/2006
Page 2

DEC 13 2006

IN THE CLAIMS

Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A disk brake unit for a motorcycle, comprising a plurality of pistons built into a caliper body having a substantially U-shaped cross section with an outer section and an inner section connected by a bridge section, an outer pad attached to the outer section, an inner pad attached to the inner section, and an outer periphery of a brake disk inserted between the outer pad and the inner pad wherein on actuation of said pistons, said outer pad and inner pad press said brake disk, wherein part of each piston ~~piston~~ projects beyond an outer peripheral edge of the brake disk to an outer side,
the outer pad and the inner pad do not project out further than the outer peripheral edge of the brake disk,
part of the bridge section projects further radially inwards than outer peripheral edges of the pistons and the projecting part of the bridge section projects between the pistons and the projecting part between the pistons extends from the inner section to the outer section of the caliper body, and
the plurality of pistons being lined up along the outer peripheral edge of the brake disk at specified intervals, ~~with part of the bridge section being caused to project between these pistons.~~

2. (Previously presented) A disk brake unit for a motorcycle, having at least one piston built into a caliper body having a substantially U-shaped cross section with an outer section and an inner section connected by a bridge section, an outer pad attached to the outer section via an outer back plate, an inner pad attached to the inner section via an inner back plate, and an outer periphery of a brake disk inserted between the outer pad

Appl. No. 10/772965
Reply to Action dated 9/14/2006
Page 3

and the inner pad wherein on actuation of said piston, said outer pad and inner pad press said brake disk, wherein

part of the piston projects beyond an outer peripheral edge of the brake disk to an outer side,

the outer pad and the inner pad do not project out further than the outer peripheral edge of the brake disk,

with the inner back plate and the outer back plate, that part corresponding to the piston is formed to have a portion which follows an outer peripheral edge of the piston, while the remaining part is formed to have a portion which follows the peripheral edge of the brake disk, and

part of the bridge section projects further inwards than the outer peripheral edge of the piston by forming the bridge section to have a portion which follows the respective back plates.

3. (Canceled)

4. (Previously presented) The disk brake unit for a motorcycle according to claim 2, wherein there are a plurality of pistons, the plurality of pistons being lined up along the outer peripheral edge of the brake disk at specified intervals, with part of the bridge section being caused to project between these pistons.

5. (Canceled)